

# Solid SKS Tire and Wheel Assemblies

from Rhino Rubber, LLC™



## Solid SKS Tire and Wheel Assemblies

- Tires sold separately or as an assembly
- Demountable solid tires
- Can re-use the wheel
- ISO certified production
- VD tread pattern is standard

### VD Pattern



TIRE SIZE	RIM (inches)	O.D. (inches)	S.W. (inches)	WEIGHT (lbs)	CAPACITY 16MPH (lbs)
30x8.5-16	5.5	30.1	7.4	120	4286
30x10-16	6.0/7.0	30.2	9.1	140	4963
32x10-20	7.0	31.8	9.2	141	7220
33x12-20	7.5	7.5/8.0	32.7	10.8	8800



**Call for a quotation and availability:**

Warehouse: **234-678-7863** • Toll Free: **877-744-6603**

# Solid SKS Tire and Wheel Assemblies

from Rhino Rubber, LLC™



## 750-16

### Tread Characteristics

- Wear resistant traction
- Increased Load Capacity
- Cut resistant

### Recommended Applications

- Asphalt or concrete surfaces
- Tight spaces where machine width is critical



## 30x10-16

### Tread Characteristics

- Disposal of mud & water
- Load Capacity
- Traction Ride

### Recommended Applications

- Muddy or dirt surfaces
- Maximum machine width is needed



## 32x10-20

### Tread Characteristics

- Disposal of mud & water
- Load Capacity
- Traction Ride

### Recommended Applications

- Muddy or dirt surfaces
- Maximum machine width is needed
- Elevate the machine higher off the ground



## 8.15-15 (28x9-15)

### Tread Characteristics

- Wear resistant traction
- Increased Load Capacity
- Cut resistant

### Recommended Applications

- Asphalt or concrete surfaces
- Tight spaces where machine width is critical



## 825-15

### Tread Characteristics

- Disposal of mud & water
- Load Capacity
- Traction Ride

### Recommended Applications

- Asphalt or concrete surfaces
- Tight spaces where machine width is critical



## 825-16

### Tread Characteristics

- Load Capacity
- Traction Ride

### Recommended Applications

- Asphalt or concrete surfaces
- Tight spaces where machine width is critical



## 33x12-20

### Tread Characteristics

- Disposal of mud & water
- Load Capacity
- Traction Ride

### Recommended Applications

- Muddy or dirt surfaces
- Maximum machine width is needed
- Elevate the machine higher off the ground



## 36x12-20

### Tread Characteristics

- Disposal of mud & water
- Good Load Capacity
- Superior Traction

### Recommended Applications

- Muddy or dirt surfaces
- Maximum machine width is needed

Easy to Find...Tough to Beat.

Warehouse: 234-678-7863

Toll Free: 877-744-6603

Fax: 888-480-8611

[www.rhinorubber.net](http://www.rhinorubber.net)

Larry Durr: 317-771-5574

Jim Sweeney: 724-504-5641

Tim Ryan: 330-354-1500

Scott Lundgren: 330-699-3511



Rhino Rubber Warehouse • 275-299 N. Arlington St. • Akron, OH 44305