

## Pneumatics

Rim size (in.)	Code	Description	Ply rating	Weight (lbs.)	O.D. (in.)	Width (in.)	Inflation P.S.I.	Load 15 mph
<b>FORKLIFT-STD</b>								
8	94007103	5.00-8 F-812	8	12	18	5.3	120	2095
8	94006977	18x7-8 F-812	16	20	18	6.8	145	3635
9	94007127	6.00-9 F-812	10	20	21	6.2	123	2910
9	94007158	6.00-9 F-812	12	20	21	6.2	145	3195
9	94006991	21x8-9 F-812	14	29	21	7.9	131	4300
10	94007165	6.50-10 F-812	10	24	23	7.3	112	3305
12	94007196	7.00-12 F-812	12	33	27	7.4	123	4540
12	94007219	7.00-12 F-812	14	36	27	7.4	131	4675
13	94007028	23x5 [-13] F-812	6	22	25	6.1	76	2535
15	94007349	7.00-15 F-812	12	40	29	7.9	120	5205
15	94007363	7.00-15 F-812	14	44	29	7.9	131	5675
15	94007370	7.50-15 F-812 30"OD	12	40	30	8.1	123	5280
15	94007387	7.50-15 F-812 30"OD	14	44	30	8.1	145	5765
15	94007271	8.15-15 F-812	14	49	28	8.5	131	6395
15	94007295	8.25-15 F-812	12	63	34	9.3	102	6615
15	94007301	8.25-15 F-812	14	64	34	9.3	116	7165
15	94007059	250-15 F-812	16	67	29	9.3	120	7385
15	94007066	250-15 F-812	20	69	29	9.3	152	8820
15	94007080	300-15 F-812	18	92	33	11.6	109	9920
20	94007622	10.00-20 PT	16	158	42	11.2	131	11025
20	94007639	10.00-20 PT HD	18	160	42	11.2	145	11685
20	94007882	12.00-20 PT HD (SM) (SMOOTH)	20	227	45	12.6	145	15100
20	94007660	12.00-20 PT HD	20	217	45	12.6	145	15100
20	94007684	12.00-20 PT HD	28	217	45	12.6	145	15100